

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Jet Pump - C type Single-Phase Product code : 13910336

Frame	: W56C	Locked rotor time	: 12s (cold) 7s (hot)
Output	: 0.5 HP (0.37 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.00/3.87-3.50 A	Protection degree	: IP55
L. R. Amperes	: 56.0/31.0-28.0 A	Cooling method	: IC411 - TEFC
LRC	: 8.0x(Code P)	Mounting	: F-1
No load current	: 4.80/2.07-2.40 A	Rotation ¹	: CCW
Rated speed	: 3500 rpm	Noise level ²	: 66.0 dB(A)
Slip	: 2.78 %	Vibration	: A
Rated torque	: 0 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 290 %	Approx. weight ³	: 9.3 kg
Breakdown torque	: 300 %		: 207N (ISO 12944 - C2)
Insulation class	: F		: Munsell N 1 - Matte
Service factor	: 1.15	Design	: N
Moment of inertia (J)	: 0.0010 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	50.0	58.0	60.0	Max. traction	: 5 kgf
Power Factor	0.59	0.69	0.76	Max. compression	: 14 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6203 2RS	6202 2RS
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	24/09/2026			

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Jet Pump - C type
Single-Phase

Product code : 13910336



Performance : 115/208-230 V 60 Hz 2P

Rated current : 7.00/3.87-3.50 A
LRC : 8.0
Rated torque : 0 kgfm
Locked rotor torque : 290 %
Breakdown torque : 300 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0010 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor :
Temperature rise : 80 K
Design : N

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	24/09/2026				