


E	Break size 18 (150 Nm)
	Without vertical jackscrews
	Brake voltage 440-480 V
	Color RAL 5009
	Painting plan 203A
Mounting NEMA F-1	
Mounting B3R(D)	



15 HP 04 Poles 60 Hz										A	
Scale 1 : 8											
HYBRISUSER										00	
ECM	LOC	SUMMARY OF MODIFICATIONS					EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER	THREE PH. MOTOR W22 BRAKE MOTOR NEMA PREM. EFF.					EXECUTED	CHECKED	RELEASED	DATE	VER
CHECKED		FRAME 254/6T IP55 TEFC					EXECUTED	CHECKED	RELEASED	DATE	VER
RELEASED							EXECUTED	CHECKED	RELEASED	DATE	VER
REL. DATE							EXECUTED	CHECKED	RELEASED	DATE	VER

E	Break size 18 (150 Nm)
	Without vertical jackscrews
	Brake voltage 440-480 V
	Color RAL 5009
	Painting plan 203A
Mounting NEMA F-1	
Mounting B3R(D)	



15 HP 04 Poles 60 Hz										A	
Scale 1 : 8											
HYBRISUSER										00	
ECM	LOC	SUMMARY OF MODIFICATIONS					EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER	THREE PH. MOTOR W22 BRAKE MOTOR NEMA PREM. EFF.					EXECUTED	CHECKED	RELEASED	DATE	VER
CHECKED		FRAME 254/6T IP55 TEFC					EXECUTED	CHECKED	RELEASED	DATE	VER
RELEASED							EXECUTED	CHECKED	RELEASED	DATE	VER
REL. DATE							EXECUTED	CHECKED	RELEASED	DATE	VER

Break size 18 (150 Nm)

Without vertical jackscrews

15 HP 04 Poles 60 Hz