

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W22 IEEE 841 NEMA Premium Efficiency Three-Phase		Product code :		14009532
Frame	:	364/5TS		Locked rotor time	:	18s (cold) 10s (hot)
Output	:	75 HP (55 kW)		Temperature rise	:	80 K
Poles	:	2		Duty cycle	:	Cont.(S1)
Frequency	:	60 Hz		Ambient temperature	:	-20°C to +40°C
Rated voltage	:	575 V		Altitude	:	1000 m.a.s.l.
Rated current	:	65.5 A		Protection degree	:	IP55
L. R. Amperes	:	432 A		Cooling method	:	IC411 - TEFC
LRC	:	6.6x(Code G)		Mounting	:	F-1
No load current	:	15.2 A		Rotation ¹	:	Both (CW and CCW)
Rated speed	:	3550 rpm		Noise level ²	:	79.0 dB(A)
Slip	:	1.39 %		Starting method	:	Direct On Line
Rated torque	:	15.3 kgfm		Approx. weight ³	:	404 kg
Locked rotor torque	:	220 %				
Breakdown torque	:	270 %				
Insulation class	:	F				
Service factor	:	1.25				
Moment of inertia (J)	:	0.5023 kgm ²				
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	92.4	93.6	93.6	Max. traction	:	262 kgf
Power Factor	0.83	0.88	0.90	Max. compression	:	667 kgf
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.4	4.9	4.7	3.1	1.8	1.0	0.6
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6314 C3		6314 C3		
Sealing	:	Inpro/Seal		Inpro/Seal		
Lubrication interval	:	4000 h		4000 h		
Lubricant amount	:	27 g		27 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	13/01/2024				1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 14009532

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 2P

Rated current	: 65.5 A	Moment of inertia (J)	: 0.5023 kgm ²
LRC	: 6.6	Duty cycle	: Cont.(S1)
Rated torque	: 15.3 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.25
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 3550 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/01/2024			