

# DATA SHEET



## Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Single-Phase

Product code : 14145114

Frame	: 182/4T	Locked rotor time	: 12s (cold) 7s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 20.5-19.0/9.50 A	Protection degree	: IP55
L. R. Amperes	: 146-135/67.5 A	Cooling method	: IC411 - TEFC
LRC	: 7.1x(Code G)	Mounting	: F-1
No load current	: 3.36-3.90/1.95 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3515 rpm	Noise level <sup>2</sup>	: 72.0 dB(A)
Slip	: 2.36 %	Starting method	: Direct On Line
Rated torque	: 1.03 kgfm	Approx. weight <sup>3</sup>	: 49.0 kg
Locked rotor torque	: 280 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0091 kgm <sup>2</sup>		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	80.0	84.0	85.5	Max. traction	: 29 kgf
Power Factor	0.96	0.99	0.99	Max. compression	: 78 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6207 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	15/01/2024		1 / 2	

# LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 Single-Phase

Product code : 14145114



Performance : 208-230/460 V 60 Hz 2P

Rated current : 20.5-19.0/9.50 A  
 LRC : 7.1  
 Rated torque : 1.03 kgfm  
 Locked rotor torque : 280 %  
 Breakdown torque : 250 %  
 Rated speed : 3515 rpm

Moment of inertia (J) : 0.0091 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor :  
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				