

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: Saw Arbor Motor Standard Efficiency Three-Phase		Product code : 14193740	
Frame	: 80L/MS	Locked rotor time	: 9s (cold) 5s (hot)		
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: S6		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 7.81 A	Protection degree	: IP54		
L. R. Amperes	: 71.8 A	Cooling method	: IC411 - TEFC		
LRC	: 9.2	Mounting	: B3R(D)		
No load current	: 3.52 A	Rotation ¹	: CCW		
Rated speed	: 3490 rpm	Noise level ²	: 62.0 dB(A)		
Slip	: 3.06 %	Starting method	: Direct On Line		
Rated torque	: 1.56 kgfm	Approx. weight ³	: 55.4 kg		
Locked rotor torque	: 400 %				
Breakdown torque	: 459 %				
Insulation class	: F				
Service factor	: 1.00				
Moment of inertia (J)	: 0.0061 kgm ²				
Design	: N				
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	85.2	87.0	87.4	Max. traction : 123 kgf	
Power Factor	0.64	0.75	0.81	Max. compression : 178 kgf	
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6307 ZZ	6207 ZZ		
Sealing	:	Without Bearing Seal	Without Bearing Seal		
Lubrication interval	:	-	-		
Lubricant amount	:	-	-		
Lubricant type	:	Mobil Polyrex EM			
Notes:					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	15/01/2024			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : Saw Arbor Motor Standard Efficiency Three-Phase Product code : 14193740

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 2P

Rated current	: 7.81 A	Moment of inertia (J)	: 0.0061 kgm ²
LRC	: 9.2	Duty cycle	: S6
Rated torque	: 1.56 kgfm	Insulation class	: F
Locked rotor torque	: 400 %	Service factor	: 1.00
Breakdown torque	: 459 %	Temperature rise	: 80 K
Rated speed	: 3490 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		2 / 2		
Date	15/01/2024			