

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Farm Duty Single-Phase Product code : 14229634

Frame	: 182/4T	Locked rotor time	: 14s (cold) 8s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 13.8 A	Protection degree	: IP55
L. R. Amperes	: 106 A	Cooling method	: IC411 - TEFC
LRC	: 7.7x(Code K)	Mounting	: F-1
No load current	: 6.70 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1745 rpm	Noise level ²	: 60.0 dB(A)
Slip	: 3.06 %	Vibration	: Not Applicable
Rated torque	: 1 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 290 %	Approx. weight ³	: 46.5 kg
Breakdown torque	: 270 %	Painting plan	: 207A (ISO 12944 - C3)
Insulation class	: F	Color	: RAL 3003
Service factor	: 1.15		
Moment of inertia (J)	: 0.0157 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	65.0	74.0	77.0	Max. traction	: 46 kgf
Power Factor	0.79	0.87	0.90	Max. compression	: 94 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6207 2RS	6206 2RS
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	00088	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	02/10/2026		Page 1 / 2	Revision

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Farm Duty Single-Phase

Product code : 14229634



Performance : 230 V 60 Hz 4P

Rated current : 13.8 A
LRC : 7.7
Rated torque : 1 kgfm
Locked rotor torque : 290 %
Breakdown torque : 270 %
Rated speed : 1745 rpm

Moment of inertia (J) : 0.0157 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	02/10/2026			