

DATA SHEET



Single Phase Induction Motor - Squirrel Cage

Customer :					
Product line : W22 Single-Phase		Product code : 14259801			
Frame	: 213/5TC	Locked rotor time	: 12s (cold) 7s (hot)		
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 30.5-28.2/14.1 A	Protection degree	: IP55		
L. R. Amperes	: 220-203/102 A	Cooling method	: IC411 - TEFC		
LRC	: 7.2x(Code G)	Mounting	: F-1		
No load current	: 5.69-6.60/3.30 A	Rotation ¹	: Both (CW and CCW)		
Rated speed	: 3510 rpm	Noise level ²	: 72.0 dB(A)		
Slip	: 2.50 %	Starting method	: Direct On Line		
Rated torque	: 1.55 kgfm	Approx. weight ³	: 75.8 kg		
Locked rotor torque	: 280 %				
Breakdown torque	: 290 %				
Insulation class	: F				
Service factor	: 1.15				
Moment of inertia (J)	: 0.0234 kgm ²				
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	78.5	84.0	85.5	Max. traction : 45 kgf	
Power Factor	0.99	0.99	0.99	Max. compression : 121 kgf	
		<u>Drive end</u>		<u>Non drive end</u>	
Bearing type	:	6308 ZZ		6206 ZZ	
Sealing	:	V'Ring		V'Ring	
Lubrication interval	:	-		-	
Lubricant amount	:	-		-	
Lubricant type	:	Mobil Polyrex EM			
Notes:					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	15/01/2024			1 / 2	

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 Single-Phase

Product code : 14259801



Performance : 208-230/460 V 60 Hz 2P

Rated current : 30.5-28.2/14.1 A
 LRC : 7.2
 Rated torque : 1.55 kgfm
 Locked rotor torque : 280 %
 Breakdown torque : 290 %
 Rated speed : 3510 rpm

Moment of inertia (J) : 0.0234 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	15/01/2024			