

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase Product code : 14301494

Frame	: 80S/MS	Locked rotor time	: 16s (cold) 9s (hot)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S6
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.43 A	Protection degree	: IP54
L. R. Amperes	: 25.1 A	Cooling method	: IC411 - TEFC
LRC	: 7.3	Mounting	: B3R(D)
No load current	: 1.65 A	Rotation ¹	: CCW
Rated speed	: 3500 rpm	Noise level ²	: 62.0 dB(A)
Slip	: 2.78 %	Vibration	: A
Rated torque	: 0 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 330 %	Approx. weight ³	: 43.0 kg
Breakdown torque	: 370 %	Painting plan	: 207A (ISO 12944 - C3)
Insulation class	: F	Color	: RAL 7022
Service factor	: 1.00	Design	: N
Moment of inertia (J)	: 0.0032 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	76.0	79.5	80.5	Max. traction	: 26 kgf
Power Factor	0.65	0.75	0.80	Max. compression	: 69 kgf

	Drive end	Non drive end
Bearing type	: 6307 ZZ	: 6207 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	08/10/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard
Efficiency Three-Phase

Product code : 14301494



Performance : 575 V 60 Hz 2P

Rated current : 3.43 A
LRC : 7.3
Rated torque : 0 kgfm
Locked rotor torque : 330 %
Breakdown torque : 370 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0032 kgm²
Duty cycle : S6
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	08/10/2026			