

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W21 Explosion Proof NEMA Premium Efficiency Three-Phase		Product code : 14325311		
Frame	: 182/4T	Locked rotor time	: 43s (cold) 24s (hot)			
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K			
Poles	: 4	Duty cycle	: Cont.(S1)			
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C			
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.			
Rated current	: 5.26 A	Protection degree	: IP55			
L. R. Amperes	: 37.3 A	Cooling method	: IC411 - TEFC			
LRC	: 7.1x(Code J)	Mounting	: F-1			
No load current	: 2.48 A	Rotation ¹	: Both (CW and CCW)			
Rated speed	: 1750 rpm	Noise level ²	: 56.0 dB(A)			
Slip	: 2.78 %	Starting method	: Direct On Line			
Rated torque	: 2.07 kgfm	Approx. weight ³	: 61.2 kg			
Locked rotor torque	: 229 %					
Breakdown torque	: 300 %					
Insulation class	: F					
Service factor	: 1.15					
Moment of inertia (J)	: 0.0156 kgm ²					
Design	: B					
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	86.5	88.5	89.5	Max. traction : 100 kgf		
Power Factor	0.59	0.71	0.79	Max. compression : 161 kgf		
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6307 2RS		6206 2RS		
Sealing	:	Oil Seal		Lip Seal		
Lubrication interval	:	-		-		
Lubricant amount	:	-		-		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	15/01/2024				1 / 3	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	15/01/2024		2 / 3	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14325311



Performance : 575 V 60 Hz 4P

Rated current : 5.26 A
 LRC : 7.1
 Rated torque : 2.07 kgfm
 Locked rotor torque : 229 %
 Breakdown torque : 300 %
 Rated speed : 1750 rpm

Moment of inertia (J) : 0.0156 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				