DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Standard Saw Arbor Motor
Product code	: 14381271

Frame	: 80S/MS
Output	: 3 HP (2.2 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 575 V
Rated current	: 3.43 A
L. R. Amperes	: 25.1 A
LRC	: 7.3 Code K
No load current	: 1.65 A
Rated speed	: 3500 rpm
Slip	: 2.78 %
Rated torque	: 0.622 kgfm
Locked rotor torque	: 330 %
Pull up torque	: 280 %
Breakdown torque	: 370 %
Insulation class	: F
Service factor	: 1.00
Moment of inertia (J)	: 0.0032 kgm²

Locked rotor time	: 9 s (hot) 16 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S6
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP54
Cooling method	: IC411 - TEFC
Mounting	: B3R(D)
Rotation[1]	: Clockwise
Noise level[2]	: 62 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 38.5 kg
Design	: N

Output	Start	50%	75%	100%
Efficiency (%)	-	76.0	79.5	80.5
Power Factor	0.78	0.65	0.75	0.8

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6307-ZZ	6207-ZZ
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Max. traction	: 29 kgf
Max. compression	: 67 kgf

Notes:

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				2026/10/26

Performed by				
Checked by			Page	Revision
Date	2026/10/26		1/2	0


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Standard Saw Arbor Motor
Product code	: 14381271



Performance	: 3 HP (2.2 kW) 575V 60Hz 2P 80S/MS

Rated current	: 3.43 A	Moment of inertia (J)	: 0.0032 kgm²
LRC	: 7.3 Code K	Duty cycle	: S6
Rated torque	: 0.622 kgfm	Insulation class	: F
Locked rotor torque	: 330 %	Service factor	: 1.00
Breakdown torque	: 370 %	Temperature rise	: 80 K
Rated speed	: 3500 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
				2026/10/26

Performed by				
Checked by			Page	Revision
Date	2026/10/26		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.