

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: Saw Arbor Motor Standard Efficiency Three-Phase		Product code : 14381272	
Frame	: 90L/MS	Locked rotor time	: 12s (cold) 7s (hot)		
Output	: 10 HP (7.5 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: S6		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 9.83 A	Protection degree	: IP54		
L. R. Amperes	: 85.5 A	Cooling method	: IC411 - TEFC		
LRC	: 8.7	Mounting	: B3R(D)		
No load current	: 3.60 A	Rotation ¹	: CW		
Rated speed	: 3480 rpm	Noise level ²	: 68.0 dB(A)		
Slip	: 3.33 %	Starting method	: Direct On Line		
Rated torque	: 2.09 kgfm	Approx. weight ³	: 75.8 kg		
Locked rotor torque	: 400 %				
Breakdown torque	: 420 %				
Insulation class	: F				
Service factor	: 1.00				
Moment of inertia (J)	: 0.0140 kgm ²				
Design	: N				
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	82.0	84.5	85.0	Max. traction : 181 kgf	
Power Factor	0.77	0.86	0.90	Max. compression : 256 kgf	
		<u>Drive end</u>		<u>Non drive end</u>	
Bearing type	:	6308 ZZ		6208 ZZ	
Sealing	:	Without Bearing Seal		Without Bearing Seal	
Lubrication interval	:	-		-	
Lubricant amount	:	-		-	
Lubricant type	:	Mobil Polyrex EM			
Notes:					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	15/01/2024			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase Product code : 14381272

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 2P

Rated current	: 9.83 A	Moment of inertia (J)	: 0.0140 kgm ²
LRC	: 8.7	Duty cycle	: S6
Rated torque	: 2.09 kgfm	Insulation class	: F
Locked rotor torque	: 400 %	Service factor	: 1.00
Breakdown torque	: 420 %	Temperature rise	: 80 K
Rated speed	: 3480 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by			2 / 2	
Date	15/01/2024			