

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line : W21 Explosion Proof NEMA Premium Efficiency Three-Phase		Product code : 14406880			
Frame : 254TC	Insulation class : F	Duty cycle : Cont.(S1)	Ambient temperature : -20°C to +40°C	Altitude : 1000 m.a.s.l.	
Protection degree : IP55	Design : B	Cooling method : IC411 - TEFC	Mounting : F-1	Rotation ¹ : Both (CW and CCW)	
		Starting method : Direct On Line	Approx. weight ³ : 151 kg	Moment of inertia (J) : 0.0974 kgm ²	
Output [HP]	15	15	15	15	
Poles	4	4	4	4	
Frequency [Hz]	60	50	50	50	
Rated voltage [V]	230/460	380	400	415	
Rated current [A]	36.8/18.4	22.1	21.3	20.8	
L. R. Amperes [A]	269/134	128	136	141	
LRC [A]	7.3x(Code J)	5.8x(Code G)	6.4x(Code G)	6.8x(Code H)	
No load current [A]	17.2/8.60	8.40	9.20	9.60	
Rated speed [RPM]	1770	1455	1460	1465	
Slip [%]	1.67	3.00	2.67	2.33	
Rated torque [kgfm]	6.15	7.48	7.46	7.43	
Locked rotor torque [%]	300	220	250	270	
Breakdown torque [%]	300	229	250	270	
Service factor	1.15	1.00	1.00	1.00	
Temperature rise	80 K	80 K	80 K	80 K	
Locked rotor time	46s (cold) 26s (hot)	45s (cold) 25s (hot)	45s (cold) 25s (hot)	45s (cold) 25s (hot)	
Noise level ²	69.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	
Efficiency (%)	25%	89.4	92.1	91.4	90.8
	50%	90.2	91.0	91.0	91.0
	75%	91.7	91.7	91.7	91.0
	100%	92.4	90.2	91.0	91.0
Power Factor	25%	0.39	0.45	0.42	0.39
	50%	0.65	0.71	0.68	0.64
	75%	0.75	0.79	0.77	0.75
	100%	0.81	0.84	0.82	0.81
Bearing type	: 6309 C3	: 6209 C3	Foundation loads		
Sealing	: Oil Seal	: Lip Seal	Max. traction	: 240 kgf	
Lubrication interval	: 20000 h	: 20000 h	Max. compression	: 391 kgf	
Lubricant amount	: 13 g	: 9 g			
Lubricant type	: Mobil Polyrex EM				
Notes USABLE @208V 40.7A SF 1.15 SFA 46.8A					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	16/01/2024			1 / 6	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	16/01/2024		2 / 6	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14406880



Performance : 230/460 V 60 Hz 4P

Rated current : 36.8/18.4 A
 LRC : 7.3
 Rated torque : 6.15 kgfm
 Locked rotor torque : 300 %
 Breakdown torque : 300 %
 Rated speed : 1770 rpm

Moment of inertia (J) : 0.0974 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14406880



Performance : 380 V 50 Hz 4P IE2

Rated current : 22.1 A
LRC : 5.8
Rated torque : 7.48 kgfm
Locked rotor torque : 220 %
Breakdown torque : 229 %
Rated speed : 1455 rpm

Moment of inertia (J) : 0.0974 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14406880



Performance : 400 V 50 Hz 4P IE2

Rated current : 21.3 A
 LRC : 6.4
 Rated torque : 7.46 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 250 %
 Rated speed : 1460 rpm

Moment of inertia (J) : 0.0974 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		5 / 6		
Date		16/01/2024		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14406880



Performance : 415 V 50 Hz 4P IE2

Rated current : 20.8 A
 LRC : 6.8
 Rated torque : 7.43 kgfm
 Locked rotor torque : 270 %
 Breakdown torque : 270 %
 Rated speed : 1465 rpm

Moment of inertia (J) : 0.0974 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.00
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		6 / 6		
Date		16/01/2024		