

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W21 Explosion Proof NEMA Premium Efficiency Three-Phase		Product code :	14407017	
Frame	:	254T		Locked rotor time	: 46s (cold) 26s (hot)	
Output	:	15 HP (11 kW)		Temperature rise	: 80 K	
Poles	:	4		Duty cycle	: Cont.(S1)	
Frequency	:	60 Hz		Ambient temperature	: -20°C to +40°C	
Rated voltage	:	575 V		Altitude	: 1000 m.a.s.l.	
Rated current	:	14.7 A		Protection degree	: IP55	
L. R. Amperes	:	107 A		Cooling method	: IC411 - TEFC	
LRC	:	7.3x(Code J)		Mounting	: F-1	
No load current	:	6.88 A		Rotation ¹	: Both (CW and CCW)	
Rated speed	:	1770 rpm		Noise level ²	: 69.0 dB(A)	
Slip	:	1.67 %		Starting method	: Direct On Line	
Rated torque	:	6.15 kgfm		Approx. weight ³	: 149 kg	
Locked rotor torque	:	300 %				
Breakdown torque	:	300 %				
Insulation class	:	F				
Service factor	:	1.15				
Moment of inertia (J)	:	0.0974 kgm ²				
Design	:	B				
Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	89.4	90.2	91.7	92.4	Max. traction	: 215 kgf
Power Factor	0.39	0.65	0.75	0.81	Max. compression	: 365 kgf
			<u>Drive end</u>		<u>Non drive end</u>	
Bearing type	:	6309 C3		6209 C3		
Sealing	:	Oil Seal		Lip Seal		
Lubrication interval	:	20000 h		20000 h		
Lubricant amount	:	13 g		9 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	15/01/2024				1 / 3	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	15/01/2024		2 / 3	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14407017



Performance : 575 V 60 Hz 4P

Rated current : 14.7 A
 LRC : 7.3
 Rated torque : 6.15 kgfm
 Locked rotor torque : 300 %
 Breakdown torque : 300 %
 Rated speed : 1770 rpm

Moment of inertia (J) : 0.0974 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date	
Performed by					
Checked by					
Date					15/01/2024
		Page	Revision		
		3 / 3			