DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : W01 - ODP - Premium Efficiency (DOE) Jet Pump - Forma J
Product code : 14477578

Frame	: W56J
Output	: 0.33 HP (0.25 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 115/208-230 V
Rated current	: 3.20/1.77-1.60 A
L. R. Amperes	: 28.2/14.1 A
LRC	: 8.8 Code L
No load current	: 1.00/0.500 A
Rated speed	: 3510 rpm
Slip	: 2.50 %
Rated torque	: 0.068 kgfm
Locked rotor torque	: 280 %
Pull up torque	: 235 %
Breakdown torque	: 300 %
Insulation class	: F
Service factor	: 1.75
Moment of inertia (J)	: 0.0011 kgm²

Locked rotor time	: 15 s (hot) 27 s (cold)
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP21
Cooling method	: IC01 - ODP
Mounting	: F-1/B14R(D)
Rotation[1]	: Counter clockwise
Noise level[2]	: 56 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 8.8 kg
Design	: N

Output	Start	50%	75%	100%
Efficiency (%)	-	56.0	64.0	70.5
Power Factor	0.93	0.97	0.97	0.97

Load type : -
Load torque : -
Load inertia (J=GD²/4) : -

	Drive end	Non drive end
Bearing type	6203-2RS	6202-2RS
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Foundation loads
Max. traction : -
Max. compression : -

Notes:

Standards

Specification : MG1 - Part 10
Test : MG1 - Part 12
Noise : MG1 - Part 9

Vibration :
Tolerance : MG1 - Part 12

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/17


Performed by				
Checked by			Page	Revision
Date	2026/11/17		1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W01 - ODP - Premium Efficiency (DOE) Jet Pump - Forma J
Product code	: 14477578



Performance	: 0.33 HP (0.25 kW) 115/208/230V 60Hz 2P W56J

Rated current	: 3.20/1.77/1.60 A	Moment of inertia (J)	: 0.0011 kgm²
LRC	: 8.8 Code L	Duty cycle	: Cont.(S1)
Rated torque	: 0.068 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.75
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 3510 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/17

Performed by				
Checked by			Page	Revision
Date	2026/11/17		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.