

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium Efficiency Three-Phase Product code : 14600945

Frame	: 449T	Locked rotor time	: 12s (cold) 7s (hot)
Output	: 300 HP (220 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 281 A	Protection degree	: IP55
L. R. Amperes	: 2218 A	Cooling method	: IC411 - TEFC
LRC	: 7.9x(Code J)	Mounting	: F-1
No load current	: 122 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1190 rpm	Noise level ²	: 70.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 183 kgfm	Approx. weight ³	: 1488 kg
Locked rotor torque	: 280 %		
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 6.09 kgm ²		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.0	95.4	95.8	Max. traction	: 4058 kgf
Power Factor	0.66	0.77	0.82	Max. compression	: 5545 kgf

	Drive end	Non drive end
Bearing type	: 6322 C3	6319 C3
Sealing	: Viton Oil Seal	Viton Seal
Lubrication interval	: 9212 h	11094 h
Lubricant amount	: 60 g	45 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3 Revision		
Checked by				
Date	15/01/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3Revision	
Checked by					
Date	15/01/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14600945



Performance : 575 V 60 Hz 6P

Rated current : 281 A
LRC : 7.9
Rated torque : 183 kgfm
Locked rotor torque : 280 %
Breakdown torque : 300 %
Rated speed : 1190 rpm

Moment of inertia (J) : 6.09 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : A

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3Revision		
Checked by				
Date	15/01/2024			