

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Super Premium Efficiency Three-Phase Product code : 14637591

Frame	: L213/5T	Locked rotor time	: 28s (cold) 16s (hot)
Output	: 10 HP (7.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 24.0/12.0 A	Protection degree	: IP55
L. R. Amperes	: 202/101 A	Cooling method	: IC411 - TEFC
LRC	: 8.4x(Code K)	Mounting	: F-1
No load current	: 11.0/5.50 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1765 rpm	Noise level ²	: 58.0 dB(A)
Slip	: 1.94 %	Vibration	: A
Rated torque	: 4 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 229 %	Approx. weight ³	: 91.0 kg
Breakdown torque	: 350 %	Painting plan	: 207A (ISO 12944 - C3)
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.25	Design	: A
Moment of inertia (J)	: 0.0751 kgm ²		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	91.7	92.4	93.0	Max. traction	: 221 kgf
Power Factor	0.00	0.66	0.78	0.84	Max. compression	: 312 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6308 ZZ	6207 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	0 h	0 h
Lubricant amount	:	0 g	0 g
Lubricant type	:	00088	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/09/2026			

Page 1 / 2
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Super Premium Efficiency
Three-Phase

Product code : 14637591



Performance : 230/460 V 60 Hz 4P

Rated current : 24.0/12.0 A
LRC : 8.4
Rated torque : 4 kgfm
Locked rotor torque : 229 %
Breakdown torque : 350 %
Rated speed : 1765 rpm

Moment of inertia (J) : 0.0751 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : A

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	29/09/2026				