



|   |
|---|
| Dipping impregnation - polyester          |
| Shaft material - stainless steel AISI 304 |
| Phenolic thermal protector - automatic    |
| Without alarm thermal protection          |
| Without switch off thermal protection     |
| Color Munsell N 1 matte black             |
| Painting plan 207N                        |
| Mounting MARKET F-1/B14R(D)               |
| Mounting F-1/B14R(D)                      |

|                        |            |   |  |  |  |  |          |         |          |      |     |
|------------------------|------------|---|--|--|--|--|----------|---------|----------|------|-----|
| 0.33 HP 02 Poles 60 Hz |            |   |  |  |  |  |          |         |          | A    |     |
| Scale 2 : 7            |            |   |  |  |  |  |          |         |          |      |     |
| HYBRISUSER             |            |   |  |  |  |  |          |         |          | 00   |     |
| ECM                    | LOC        | SUMMARY OF MODIFICATIONS                                    |  |  |  |  | EXECUTED | CHECKED | RELEASED | DATE | VER |
| EXECUTED               | HYBRISUSER | SINGLE PH. MOTOR ROLLED STEEL JET PUMP THREADED PRELIMINARY |  |  |  |  | WDD      | 00      | PREVIEW  |      |     |
| CHECKED                |            | FRAME W56J IP55 TEFC  |  |  |  |  | WDD      | 00      | PREVIEW  |      |     |
| RELEASED               |            |   |  |  |  |  | WDD      | 00      | PREVIEW  |      |     |
| REL. DATE              |            |   |  |  |  |  | WDD      | 00      | PREVIEW  |      |     |
| SHEET                  |            |   |  |  |  |  | 1 / 1    |         |          |      |     |