

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: W22 IEEE 841 NEMA Premium Efficiency Three-Phase			Product code : 14913623	
Frame	:	284/6TC		Locked rotor time	:	45s (cold) 25s (hot)
Output	:	15 HP (11 kW)		Temperature rise	:	80 K
Poles	:	8		Duty cycle	:	Cont.(S1)
Frequency	:	60 Hz		Ambient temperature	:	-20°C to +40°C
Rated voltage	:	575 V		Altitude	:	1000 m.a.s.l.
Rated current	:	15.7 A		Protection degree	:	IP55
L. R. Amperes	:	86.2 A		Cooling method	:	IC411 - TEFC
LRC	:	5.5x(Code G)		Mounting	:	F-1
No load current	:	7.84 A		Rotation <sup>1</sup>	:	Both (CW and CCW)
Rated speed	:	880 rpm		Noise level <sup>2</sup>	:	54.0 dB(A)
Slip	:	2.22 %		Starting method	:	Direct On Line
Rated torque	:	12.4 kgfm		Approx. weight <sup>3</sup>	:	187 kg
Locked rotor torque	:	200 %				
Breakdown torque	:	229 %				
Insulation class	:	F				
Service factor	:	1.25				
Moment of inertia (J)	:	0.3448 kgm <sup>2</sup>				
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	85.5	90.0	90.2	Max. traction : 313 kgf		
Power Factor	0.62	0.72	0.78	Max. compression : 500 kgf		
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
10.3	8.2	7.6	5.5	3.7	2.7	1.8
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6311 C3		6211 C3		
Sealing	:	Inpro/Seal		Inpro/Seal		
Lubrication interval	:	20000 h		20000 h		
Lubricant amount	:	18 g		11 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	15/01/2024				1 / 2	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase      Product code : 14913623

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 8P

Rated current : 15.7 A	Moment of inertia (J) : 0.3448 kgm <sup>2</sup>
LRC : 5.5	Duty cycle : Cont.(S1)
Rated torque : 12.4 kgfm	Insulation class : F
Locked rotor torque : 200 %	Service factor : 1.25
Breakdown torque : 229 %	Temperature rise : 80 K
Rated speed : 880 rpm	Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	15/01/2024			