

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase Product code : 14943075

Frame	: 56C	Locked rotor time	: 14s (cold) 8s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 16.8/9.29-8.40 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 144/79.9-72.2 A	Mounting	: F-1
LRC	: 8.6x(Code K)	Rotation ¹	: Both (CW and CCW)
No load current	: 5.00/2.16-2.50 A	Noise level ²	: 58.0 dB(A)
Rated speed	: 3500 rpm	Vibration	: A
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 0 kgfm	Approx. weight ³	: 16.5 kg
Locked rotor torque	: 250 %		: 207N (ISO 12944 - C2)
Breakdown torque	: 280 %	Design	: L
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0032 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	76.0	81.0	82.9	Max. traction	: 28 kgf
Power Factor	0.90	0.94	0.94	Max. compression	: 46 kgf

	Drive end	Non drive end
Bearing type	: 6204 ZZ	: 6202 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/09/2026			

Page 1 / 2
Revision

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase

Product code : 14943075



Performance : 115/208-230 V 60 Hz 2P

Rated current : 16.8/9.29-8.40 A
LRC : 8.6
Rated torque : 0 kgfm
Locked rotor torque : 250 %
Breakdown torque : 280 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0032 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor :
Temperature rise : 80 K
Design : L

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	24/09/2026				