DATA SHEET

Three Phase Induction Motor - Squirrel Cage

PRELIMINARY DOCUMENT

Customer	:

Product line	: W22 P-base - Nema Premium Efficiency
Product code	: 15010603

Frame	: 182HP	Locked rotor time	: 16 s (hot) 29 s (cold)
Output	: 1.5 HP (1.1 kW)	Temperature rise[4]	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l
Rated current	: 2.03 A	Protection degree	: IP55
L. R. Amperes	: 15.8 A	Cooling method	: IC411 - TEFC
LRC	: 7.8 Code M	Mounting	: V1
No load current	: 1.30 A	Rotation[1]	: Both
Rated speed	: 1170 rpm	Noise level[2]	: 52 dB(A)
Slip	: 2.50 %	Starting method	: Direct On Line
Rated torque	: 0.930 kgfm	Approx. weight[3]	: 31.9 kg
Locked rotor torque	: 320 %	Design	: B
Pull up torque	: 270 %		
Breakdown torque	: 400 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0206 kgm²		

Output	Start	50%	75%	100%
Efficiency (%)	-	84.0	86.5	87.5
Power Factor	0.48	0.45	0.54	0.62

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6308-ZZ	6206-ZZ
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	POLYUREA BASED GREASE	

Notes:

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
13.43	10.31	9.29	8.80	5.81	4.76	3.49

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				2026/10/22

Performed by				
Checked by			Page	Revision
Date	2026/10/22		1/2	0


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

PRELIMINARY DOCUMENT

Customer	:
Product line	: W22 P-base - Nema Premium Efficiency
Product code	: 15010603



Performance	: 1.5 HP (1.1 kW) 575V 60Hz 6P 182HP

Rated current	: 2.03 A	Moment of inertia (J)	: 0.0206 kgm²
LRC	: 7.8 Code M	Duty cycle	: Cont.(S1)
Rated torque	: 0.930 kgfm	Insulation class	: F
Locked rotor torque	: 320 %	Service factor	: 1.25
Breakdown torque	: 400 %	Temperature rise	: 80 K
Rated speed	: 1170 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
				2026/10/22

Performed by				
Checked by			Page	Revision
Date	2026/10/22		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.