

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line	: W22 Brake Motor NEMA Premium Efficiency Three-Phase					
Product code	: 15200457					
Frame : 324/6T Output : 25 HP (18.5 kW) Poles : 6 Frequency : 60 Hz Rated voltage : 575 V Rated current : 24.6 A L. R. Amperes : 153 A LRC : 6.2x(Code G) No load current : 11.2 A Rated speed : 1180 rpm Slip : 1.67 % Rated torque : 15.4 kgfm Locked rotor torque : 210 % Breakdown torque : 260 % Insulation class : F Service factor : 1.25 Moment of inertia (J) : 0.4843 kgm ² Design : B	Locked rotor time : 46s (cold) 26s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : F-1 Rotation ¹ : Both (CW and CCW) Noise level ² : 62.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 294 kg					
Output	50% 75% 100%					
Efficiency (%)	92.4 93.0 93.0					
Power Factor	0.65 0.77 0.81					
Foundation loads						
Max. traction : 356 kgf						
Max. compression : 650 kgf						
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
7.3	6.0	5.8	3.8	2.6	1.8	1.2
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6312 C3		6212 C3		
Sealing	:	V'Ring		Lip Seal		
Lubrication interval	:	20000 h		20000 h		
Lubricant amount	:	21 g		13 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	16/01/2024				1 / 3	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Brake information

Voltage: 525-575 V
Brake Torque: 40.8 kgfm

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	16/01/2024		2 / 3	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 Brake Motor NEMA Premium Efficiency Product code : 15200457
 Three-Phase



Performance : 575 V 60 Hz 6P

Rated current : 24.6 A
 LRC : 6.2
 Rated torque : 15.4 kgfm
 Locked rotor torque : 210 %
 Breakdown torque : 260 %
 Rated speed : 1180 rpm

Moment of inertia (J) : 0.4843 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				