

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W21 Explosion Proof NEMA Premium Efficiency Three-Phase      Product code : 15466193

Frame	: 586/7T	Locked rotor time	: 43s (cold) 24s (hot)
Output	: 450 HP (330 kW)	Temperature rise	: 105 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 401 A	Protection degree	: IP55
L. R. Amperes	: 2605 A	Cooling method	: IC411 - TEFC
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 96.8 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 1787 rpm	Noise level <sup>2</sup>	: 83.0 dB(A)
Slip	: 0.72 %	Starting method	: Direct On Line
Rated torque	: 183 kgfm	Approx. weight <sup>3</sup>	: 1998 kg
Locked rotor torque	: 180 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 8.99 kgm <sup>2</sup>		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.8	96.2	96.2	Max. traction	: 1503 kgf
Power Factor	0.81	0.85	0.86	Max. compression	: 3501 kgf

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: 6322 C3	6319 C3
Sealing	: Viton Oil Seal	Viton Seal
Lubrication interval	: 5138 h	7038 h
Lubricant amount	: 60 g	45 g
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	16/01/2024		1 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	16/01/2024		2 / 3	

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W21 Explosion Proof NEMA Premium  
Efficiency Three-Phase

Product code : 15466193



Performance : 575 V 60 Hz 4P

Rated current : 401 A  
LRC : 6.5  
Rated torque : 183 kgfm  
Locked rotor torque : 180 %  
Breakdown torque : 200 %  
Rated speed : 1787 rpm

Moment of inertia (J) : 8.99 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.15  
Temperature rise : 105 K  
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				