

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 Close Coupled Pump JM NEMA Premium Efficiency Three-Phase Product code : 15721068

Frame	: 143/5JM	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 2.05 A	Protection degree	: IP55
L. R. Amperes	: 18.2 A	Cooling method	: IC411 - TEFC
LRC	: 8.9x(Code L)	Mounting	: F-1
No load current	: 0.720 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3475 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 3.47 %	Starting method	: Direct On Line
Rated torque	: 0.415 kgfm	Approx. weight ³	: 24.5 kg
Locked rotor torque	: 350 %		
Breakdown torque	: 380 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0026 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	82.5	85.5	85.5	Max. traction	: 33 kgf
Power Factor	0.71	0.80	0.86	Max. compression	: 57 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
15.9	12.2	10.9	8.2	4.8	3.1	1.9

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6206 ZZ	6204 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/01/2024		1 / 2	

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer : _____

Product line : W22 Close Coupled Pump JM NEMA
Premium Efficiency Three-Phase

Product code : 15721068

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 2P

Rated current : 2.05 A
LRC : 8.9
Rated torque : 0.415 kgfm
Locked rotor torque : 350 %
Breakdown torque : 380 %
Rated speed : 3475 rpm

Moment of inertia (J) : 0.0026 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/01/2024			