

DATA SHEET



Single Phase Induction Motor - Squirrel Cage

Customer :

Product line : Compressor Duty Single-Phase Product code : 15842173

Frame	: G56HZ	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 105 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 21.0-19.1 A	Protection degree	: IP21
L. R. Amperes	: 137-124 A	Cooling method	: IC01 - ODP
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 3.19-3.70 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3455 rpm	Starting method	: Direct On Line
Slip	: 4.03 %	Approx. weight ³	: 22.1 kg
Rated torque	: 1.05 kgfm		
Locked rotor torque	: 220 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0030 kgm ²		

Output	50%	75%	100%	Foundation loads
Efficiency (%)	83.0	85.0	85.0	Max. traction
Power Factor	0.99	0.99	0.99	Max. compression

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6203 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	27/07/2024		1 / 2	


LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : Compressor Duty Single-Phase Product code : 15842173



Performance : 208-230 V 60 Hz 2P

Rated current : 21.0-19.1 A
 LRC : 6.5
 Rated torque : 1.05 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 200 %
 Rated speed : 3455 rpm

Moment of inertia (J) : 0.0030 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 105 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	27/07/2024			