

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase Product code : 17009745

Frame	: 56	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Frequency	: 60 Hz	Duty cycle	: Cont.(S1)
Rated voltage	: 115/208-230 V	Ambient temperature	: -20°C to +40°C
Poles	: 4	Altitude	: 1000 m.a.s.l.
Rated current	: 13.0/7.10-6.50 A	Protection degree	: IP55
	: 6.9x(Code H)	Cooling method	: IC411 - TEFC
Rated speed	: 1725 rpm	Mounting	: F-1
Rated torque	: 0.631 kgfm	Rotation ¹	: Both (CW and CCW)
Insulation class	: F	Noise level ²	: 54.0 dB(A)
Service factor	: 1.15	Starting method	: Direct On Line
Moment of inertia (J)	: 0.0060 kgm ²	Approx. weight ³	: 19.5 kg

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	0.000	69.0	75.0	77.0	Max. traction : 41 kgf
Power Factor	0.00	0.90	0.93	0.94	Max. compression : 60 kgf

	Drive end	Non drive end
Bearing type	: 6204 ZZ	6202 ZZ
Sealing	: V'Ring	V'Ring
Lubrication interval	: 0 h	0 h
Lubricant amount	: 0 g	0 g
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.


- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		1 / 2		
Date	11/05/2026			

LOAD PERFORMANCE CURVE


Single Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : Rolled Steel Single-Phase

Product code : 17009745



Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date				