DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Special Motor
Product code	: 17114236

Frame	: 213LP
Output	: 5 HP (3.7 kW)
Poles	: 4
Frequency	: 60 Hz
Rated voltage	: 575 V
Rated current	: 5.19 A
L. R. Amperes	: 34.3 A
LRC	: 6.6 Code H
No load current	: 2.31 A
Rated speed	: 1765 rpm
Slip	: 1.94 %
Rated torque	: 2.06 kgfm
Locked rotor torque	: 210 %
Pull up torque	: 170 %
Breakdown torque	: 280 %
Insulation class	: F
Service factor	: 1.25
Moment of inertia (J)	: 0.0413 kgm²

Locked rotor time	: 36 s (hot) 64 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: V1
Rotation[1]	: Both
Noise level[2]	: 58 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 93.0 kg
Design	: B

Output	Start	50%	75%	100%
Efficiency (%)	-	89.5	89.5	89.5
Power Factor	0.47	0.63	0.75	0.8

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6309-C3	7306BECB
Bearing type #2	-	7306BECB
Lubrication interval	14395 h	16157 h
Lubricant amount	13 g	7 g
Lubricant amount #2	-	7 g
Lubricant type	MOBIL POLYREX EM	

Notes:
In Line Extra Thrust
NEMA Premium Efficiency

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.38	9.35	8.43	6.22	4.16	3.01	2.10

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				09/02/2023

Performed by	julios	35852/2023	
Checked by	AUTOMATICO	Page	Revision
Date	09/02/2023	1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: Special Motor
Product code	: 17114236



Performance	: 5 HP (3.7 kW) 575V 60Hz 4P 213LP

Rated current	: 5.19 A	Moment of inertia (J)	: 0.0413 kgm²
LRC	: 6.6 Code H	Duty cycle	: Cont.(S1)
Rated torque	: 2.06 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.25
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1765 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
				09/02/2023

Performed by	julios		35852/2023	
Checked by	AUTOMATICO		Page	Revision
Date	09/02/2023		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.