

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Brake Motor NEMA Premium Efficiency Three-Phase Product code : 17230020

Frame	: 143/5TC	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.72/2.86 A	Protection degree	: IP55
L. R. Amperes	: 47.5/23.7 A	Cooling method	: IC411 - TEFC
LRC	: 8.3x(Code L)	Mounting	: F-1
No load current	: 3.46/1.73 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1750 rpm	Noise level ²	: 51.0 dB(A)
Slip	: 2.78 %	Starting method	: Direct On Line
Rated torque	: 0.829 kgfm	Approx. weight ³	: 23.0 kg
Locked rotor torque	: 280 %		
Breakdown torque	: 350 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0066 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	85.0	86.0	86.5	Max. traction	: 68 kgf
Power Factor	0.55	0.68	0.76	Max. compression	: 97 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
16.9	13.4	12.0	12.1	8.7	7.9	5.9

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	: 6205 ZZ	: 6204 ZZ
Sealing	: V'Ring	: Lip Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: 00088	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	14/08/2026			
			Page	Revision
			1 / 3	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Brake information

Voltage: 440-480 V
Brake Torque: 1.63 kgfm

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 3		Revision
Checked by					
Date	14/08/2026				


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Brake Motor NEMA Premium Product code : 17230020
Efficiency Three-Phase



Performance : 230/460 V 60 Hz 4P

Rated current : 5.72/2.86 A
LRC : 8.3
Rated torque : 0.829 kgfm
Locked rotor torque : 280 %
Breakdown torque : 350 %
Rated speed : 1750 rpm

Moment of inertia (J) : 0.0066 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	14/08/2026				