

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line		: W22 NEMA Premium Efficiency Three-Phase		Product code : 17370101	
Frame	: 586/7TZ		Locked rotor time	: 46s (cold) 26s (hot)	
Output	: 300 HP (220 kW)		Temperature rise	: 80 K	
Frequency	: 60 Hz		Duty cycle	: Cont.(S1)	
Rated voltage	: 575 V		Ambient temperature	: -20°C to +40°C	
Poles	: 6		Altitude	: 1000 m.a.s.l.	
Rated current	: 307 A		Protection degree	: IP55	
	: 7.0x(Code J)		Cooling method	: IC411 - TEFC	
Rated speed	: 1194 rpm		Mounting	: F-1	
Rated torque	: 182 kgfm		Rotation <sup>1</sup>	: Both (CW and CCW)	
Insulation class	: F		Noise level <sup>2</sup>	: 77.0 dB(A)	
Service factor	: 1.15		Starting method	: Direct On Line	
Moment of inertia (J)	: 10.4 kgm <sup>2</sup>		Approx. weight <sup>3</sup>	: 1753 kg	
Design	: A				
Output	25%	50%	75%	100%	
Efficiency (%)	0.000	94.5	95.4	95.8	
Power Factor	0.00	0.57	0.69	0.75	
Foundation loads					
Max. traction : 2369 kgf					
Max. compression : 4122 kgf					
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	NU-324 C3	6319 C3		
Sealing	:	Taconite Labyrinth	Taconite Labyrinth		
Lubrication interval	:	6000 h	13000 h		
Lubricant amount	:	72 g	45 g		
Lubricant type	:	Mobil Polyrex EM			
Notes					
W22 NEMA Premium Efficiency Crusher Duty					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	28/05/2026			1 / 3	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

### Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

### Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	28/05/2026		2 / 3	

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 17370101



Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 3 / 3	Revision
Checked by				
Date	28/05/2026			