

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 JP Pump High Efficiency Three-Phase Product code : 17699809

Frame	: 284/6JP	Locked rotor time	: 21s (cold) 12s (hot)
Output	: 40 HP (30 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 416 V	Altitude	: 1000 m.a.s.l.
Rated current	: 53.4 A	Protection degree	: IP23
L. R. Amperes	: 320 A	Cooling method	: IC01 - ODP
LRC	: 6.0x(Code G)	Mounting	: W-6
No load current	: 17.2 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3535 rpm	Noise level ²	: 73.0 dB(A)
Slip	: 1.81 %	Starting method	: Direct On Line
Rated torque	: 8.21 kgfm	Approx. weight ³	: 147 kg
Locked rotor torque	: 210 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0746 kgm ²		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	91.7	91.7	91.7	Max. traction	: 0 kgf
Power Factor	0.00	0.74	0.82	0.85	Max. compression	: 0 kgf

	Drive end	Non drive end
Bearing type	: 6311 Z C3	6211 Z C3
Sealing	: Without Bearing Seal	Without Bearing Seal
Lubrication interval	: 4500 h	4500 h
Lubricant amount	: 18 g	11 g
Lubricant type	Mobil Polyrex EM	

Notes
W40 High Efficiency
UL Fire Pump

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	14/07/2026		Page 1 / 2	Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 JP Pump High Efficiency
Three-Phase

Product code : 17699809



Performance : 416 V 60 Hz 2P

Rated current : 53.4 A
LRC : 6.0
Rated torque : 8.21 kgfm
Locked rotor torque : 210 %
Breakdown torque : 200 %
Rated speed : 3535 rpm

Moment of inertia (J) : 0.0746 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					