

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 17980375

Frame	: 132S	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 7.26 A	Protection degree	: IP55
L. R. Amperes	: 69.7 A	Cooling method	: IC411 - TEFC
LRC	: 9.6	Mounting	: B34L(E)
No load current	: 3.20 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level ²	: 68.0 dB(A)
Slip	: 1.25 %	Vibration	: A
Rated torque	: 1 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 290 %	Approx. weight ³	: 65.0 kg
Breakdown torque	: 409 %		: 207A (ISO 12944 - C3)
Insulation class	: F		: RAL 5009
Service factor	: 1.25	Design	: N
Moment of inertia (J)	: 0.0216 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	86.5	89.0	89.5	Max. traction	: 84 kgf
Power Factor	0.69	0.80	0.85	Max. compression	: 148 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
11.0	7.9	6.8	7.0	4.0	3.2	1.9

	Drive end	Non drive end
Bearing type	: 6308 ZZ	: 6207 ZZ
Sealing	: V'Ring	: V'Ring
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/09/2026		Page 1 / 2	Revision


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 17980375



Performance : 575 V 60 Hz 2P

Rated current : 7.26 A
LRC : 9.6
Rated torque : 1 kgfm
Locked rotor torque : 290 %
Breakdown torque : 409 %
Rated speed : 3555 rpm

Moment of inertia (J) : 0.0216 kgm²
Duty cycle : S1
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : N

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	24/09/2026				