

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Super Premium Efficiency Three-Phase Product code : 18431197

Frame	: 447/9T	Locked rotor time	: 39s (cold) 22s (hot)
Output	: 150 HP (110 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 143 A	Protection degree	: IP55
L. R. Amperes	: 1074 A	Cooling method	: IC411 - TEFC
LRC	: 7.5x(Code J)	Mounting	: F-1
No load current	: 68.8 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1190 rpm	Noise level ²	: 70.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 91.5 kgfm	Approx. weight ³	: 1023 kg
Locked rotor torque	: 260 %		
Breakdown torque	: 320 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 6.13 kgm ²		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.0	95.8	96.2	Max. traction	: 1925 kgf
Power Factor	0.62	0.74	0.80	Max. compression	: 3197 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.2	3.2	2.6	2.7	1.8	1.4	0.9

	Drive end	Non drive end
Bearing type	: 6322 C3	6319 C3
Sealing	: WSeal	WSeal
Lubrication interval	: 11000 h	13000 h
Lubricant amount	: 60 g	45 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	07/07/2026		Page 1 / 2	Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Super Premium Efficiency
Three-Phase

Product code : 18431197



Performance : 575 V 60 Hz 6P

Rated current : 143 A
LRC : 7.5
Rated torque : 91.5 kgfm
Locked rotor torque : 260 %
Breakdown torque : 320 %
Rated speed : 1190 rpm

Moment of inertia (J) : 6.13 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : A

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					