

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Nema Premium Efficiency Product code : 18193986

Frame	: 213/5TC	Locked rotor time	: 18 s (hot) 32 s (cold)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 3280 ft
Rated current	: 7.17 A	Protection degree	: IP55
L. R. Amperes	: 51.6 A	Cooling method	: IC411 - TEFC
LRC	: 7.2	Mounting	: F-1/B14R(D)
No load current	: 3.28 A	Rotation <sup>1</sup>	: Both
Rated speed	: 1770 rpm	Noise level <sup>2</sup>	: 60.0 dB(A)
Slip	: 1.67 %	Vibration class	: A
Rated torque	: 21.9 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 230 %	Approx. weight <sup>3</sup>	: 120 lb
Pull up torque	: 230 %	Painting plan	: 207N
Breakdown torque	: 300 %	Color	: MUNSELL N 1 - MATTE
Insulation class	: F	Design	: B
Service factor	: 1.15		
Moment of inertia (J)	: 0.8899 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	90.2	91.0	91.7	Load torque	: -
Power Factor	0.68	0.78	0.84	Load inertia (J=GD <sup>2</sup> /4)	: -

	Drive end	Non drive end	Foundation loads	
Bearing type #1	6208-ZZ	6206-ZZ	Max. traction	:
Bearing type #2	-	-	Max. compression	:
Lubrication interval	-	-		
Lubricant amount #1	-	-		
Lubricant amount #2	-	-		
Lubricant type	MOBIL POLYREX EM			

Notes  
See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
8.8	7.4	6.9	4.5	3.1	2.1	1.6

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1859555675		
Checked by	AUTOMATICO	Page	Rev.	
Date	11/06/2026	1 / 2	0	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Nema Premium Efficiency      Product code : 18193986

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	185955675		
Checked by	AUTOMATICO	Page	Rev.	
Date	11/06/2026	2 / 2	0	