

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W22 - Nema Super Premium

Frame	: 254/6TC	Locked rotor time	: 31 s (hot) 56 s (cold)
Output	: 15 HP (11 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 230/460 V	Altitude	: 3280 ft
Rated current	: 35.6/17.8 A	Protection degree	: IP55
L. R. Amperes	: 303/151 A	Cooling method	: IC411 - TEFC
LRC	: 8.5	Mounting	: F-1
No load current	: 16.2/8.10 A	Rotation ¹	: Both
Rated speed	: 1780 rpm	Noise level ²	: 64.0 dB(A)
Slip	: 1.11 %	Vibration class	: A
Rated torque	: 43.6 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 320 %	Coupling	: Direct
Pull up torque	: 270 %	Approx. weight ³	: 327 lb
Breakdown torque	: 350 %	Painting plan	: 203A
Insulation class	: F	Color	: RAL 6002
Service factor	: 1.25	Design	: A
Moment of inertia (J)	: 3.66 sq.ft.lb		

Output	50%	75%	100%
Efficiency (%)	91.7	93.0	93.6
Power Factor	0.66	0.76	0.83

Load type	: -
Load torque	: -
Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end
Bearing type #1	6309-C3	6209-C3
Bearing type #2	-	-
Lubrication interval	20000 h	20000 h
Lubricant amount #1	13 g	9 g
Lubricant amount #2	-	-
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Max. traction	: 2536 N
Max. compression	: 3989 N

Notes

See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.5	4.8	4.1	3.9	2.4	1.8	1.1

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1870626546	
Checked by	AUTOMATICO			Page	Rev.
Date	07/07/2026			1 / 2	0

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W22 - Nema Super Premium

Notes
USABLE @208V 39.4A SF 1.15 SFA 45.3A

Customer information
CSA
Class I, Div 2, Gr A, B, C, D, 1.15SF - T3
Class I, Zone 2, IIC, 1.15SF - T3
Class II, Div 2, Gr F, G - T4
For use on PWM: Gr. A, B, C, D, F,
VT 1000:1, CT 20:1, 1.00SF - T3A

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.

(1) Looking the motor from the shaft end.

(2) Measured at 1m and with tolerance of +3dB(A).

(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1870626546	
Checked by	AUTOMATICO			Page	Rev.
Date	07/07/2026			2 / 2	0