

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 19337726

Frame	: 56Z	Locked rotor time	: 16 s (hot) 28 s (cold)
Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 115/208-230 V	Altitude	: 3280 ft
Rated current	: 6.09/2.90-3.04 A	Protection degree	: IP55
L. R. Amperes	: 36.5/17.0-18.2 A	Cooling method	: IC411 - TEFC
LRC	: 6.0 Code P	Mounting	: F-1/B34R(D)
No load current	: 5.00/2.20-2.50 A	Rotation ¹	: Both
Rated speed	: 1725 rpm	Noise level ²	: 54.0 dB(A)
Slip	: 4.17 %	Vibration class	: A
Rated torque	: 1.01 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 430.0 %	Approx. weight ³	: 21.6 lb
Pull up torque	: 365.0 %	Painting plan	: 207N
Breakdown torque	: 310.0 %	Color	: MUNSELL N 1 - MATTE
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0570 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	45.0	53.0	59.5	Load torque	: -
Power Factor	0.45	0.53	0.60	Load inertia (J=GD ² /4)	: -

	Drive end	Non drive end	Foundation loads
Bearing type	6204-ZZ	6202-ZZ	Max. traction
Lubrication interval	-	-	Max. compression
Lubricant amount	-	-	
Lubricant type	MOBIL POLYREX EM		

Notes
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1847863688		
Checked by	AUTOMATICO	Page	Rev.	
Date	13/05/2026	1 / 2	0	

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 19337726

Thermal protection ID

Application

Type

Quantity

Sensing Temperature

Notes

Standards

Specification : MG1 - Part 10
Test : MG1 - Part 12
Noise : MG1 - Part 9

Vibration : MG1 - Part 7
Tolerance : MG1 - Part 12

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1847863688		
Checked by	AUTOMATICO	Page	Rev.	
Date	13/05/2026	2 / 2	0	