

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 17009743

Frame	: 56Z	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1/B14R(D)
Duty cycle	: S1	Rotation ¹	: Both
Ambient temperature	: -20 °C to +40 °C	Starting method	: Direct On Line
Altitude	: 3280 ft	Approx. weight ³	: 35.3 lb
Protection degree	: IP55	Moment of inertia (J)	: 0.1092 sq.ft.lb

Output	1 HP (0.75 kW)	1 HP (0.75 kW)	
Poles	4	4	
Frequency	60 Hz	50 Hz	
Rated voltage	115/208-230 V	110/220 V	
Rated current	9.29/4.95-4.64 A	11.4/5.70 A	
L. R. Amperes	74.3/33.0-37.1 A	72.0/36.0 A	
LRC	8.0 x Code K	6.3 x Code J	
No load current	3.25/1.30-1.70 A	6.85/3.45 A	
Rated speed	1745 rpm	1430 rpm	
Slip	3.06 %	4.67 %	
Rated torque	3.01 ft.lb	3.67 ft.lb	
Locked rotor torque	310.0 %	280.0 %	
Pull up torque	260.0 %	235.0 %	
Breakdown torque	280.0 %	250.0 %	
Service factor	1.15	1.00	
Temperature rise	80 K	105 K	
Noise level ²	54.0 dB(A)	54.0 dB(A)	
Locked rotor time (hot)	18 s	12 s	
Locked rotor time (cold)	32 s	21 s	
Efficiency (%)	50%	62.0	57.0
	75%	71.0	65.0
	100%	75.5	70.0
Power Factor	50%	0.87	0.60
	75%	0.91	0.65
	100%	0.93	0.75

Bearing type Lubrication interval Lubricant amount Lubricant type	Drive end	Non drive end	Foundation loads
	6204-ZZ	6202-ZZ	Max. traction :-
	-	-	Max. compression :-
	-	-	Load type :-
	MOBIL POLYREX EM		Load torque :-
			Load inertia (J=GD ² /4) :-

Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq		1850042162	
Checked by	AUTOMATICO		Page	Rev.
Date	19/05/2026		1 / 2	0

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 17009743

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1850042162		
Checked by	AUTOMATICO	Page	Rev.	
Date	19/05/2026	2 / 2	0	