

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEAO - Grain Dryer Product code : 18366731

Frame	: 182/4TZ	Cooling method	: IC418 - TEAO
Insulation class	: F	Minimum air speed over motor	: 16.8 m/s
Duty cycle	: S1	Mounting	: F-3/B3T
Ambient temperature	: -20 °C to +40 °C	Rotation ¹	: Both
Altitude	: 3280 ft	Starting method	: Direct On Line
Protection degree	: IP55	Approx. weight ³	: 0.0 lb
		Moment of inertia (J)	: 0.0000 sq.ft.lb

Output	7.5 HP (5.5 kW)	10 HP (7.5 kW)	
Poles	2	2	
Frequency	60 Hz	60 Hz	
Rated voltage	230 V	230 V	
Rated current	30.0 A	39.5 A	
L. R. Amperes	315 A	316 A	
LRC	10.5	8.0	
No load current	12.3 A	12.3 A	
Rated speed	3540 rpm	3490 rpm	
Slip	1.67 %	3.06 %	
Rated torque	11.0 ft.lb	14.8 ft.lb	
Locked rotor torque	250 %	190 %	
Pull up torque	210 %	160 %	
Breakdown torque	470 %	340 %	
Service factor	1.00	1.00	
Temperature rise	105 K	105 K	
Noise level ²	72.0 dB(A)	72.0 dB(A)	
Locked rotor time (hot)	9 s	6 s	
Locked rotor time (cold)	16 s	11 s	
Efficiency (%)	50%	73.1	78.0
	75%	79.8	83.0
	100%	83.0	85.0
Power Factor	50%	0.92	0.94
	75%	0.95	0.96
	100%	0.96	0.97

	Drive end	Non drive end	Foundation loads
Bearing type	6206-ZZ	6205-ZZ	Max. traction :-
Lubrication interval	-	-	Max. compression :-
Lubricant amount	-	-	Load type :-
Lubricant type	MOBIL POLYREX EM		Load torque :-
			Load inertia (J=GD ² /4) :-

Notes
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq			1847389405
Checked by	AUTOMATICO		Page	Rev.
Date	12/05/2026		1 / 2	0

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEAO - Grain Dryer

Product code : 18366731

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155°C

Notes

Standards	Specification	Vibration
	: MG1 - Part 10	: MG1 - Part 7
	Test : MG1 - Part 12	Tolerance : MG1 - Part 12
	Noise : MG1 - Part 9	

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1847389405		
Checked by	AUTOMATICO	Page	Rev.	
Date	12/05/2026	2 / 2	0	