

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP - Premium Efficiency (DOE)

Frame	: 48	Locked rotor time	: 17 s (hot) 31 s (cold)
Output	: 0.33 HP (0.25 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 115/208-230 V	Altitude	: 3280 ft
Rated current	: 4.12/2.32-2.06 A	Protection degree	: IP21
L. R. Amperes	: 30.1/16.9-15.0 A	Cooling method	: IC01 - ODP
LRC	: 7.3	Mounting	: F-1/B3R(D)
No load current	: 3.10/1.34-1.55 A	Rotation ¹	: Both
Rated speed	: 1745 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 3.06 %	Vibration class	: A
Rated torque	: 0.977 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 320 %	Approx. weight ³	: 20.3 lb
Pull up torque	: 270 %	Color	: PRIMER ONLY
Breakdown torque	: 300 %	Design	: N
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0451 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	61.0	68.0	72.4	Load torque	: -
Power Factor	0.53	0.67	0.73	Load inertia (J=GD ² /4)	: -

Bearing type	Drive end	Non drive end	Foundation loads	
	6203-ZZ	6202-ZZ		
Lubrication interval	-	-	Max. traction	: -
Lubricant amount	-	-	Max. compression	: -
Lubricant type	MOBIL POLYREX EM			

Notes
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1848515392	
Checked by	AUTOMATICO			Page	Rev.
Date	14/05/2026			1 / 2	0

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP - Premium Efficiency (DOE)

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq		1848515392	
Checked by	AUTOMATICO		Page	Rev.
Date	14/05/2026		2 / 2	0