

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W22

Frame	: 182/4TC	Locked rotor time	: 8 s (hot) 14 s (cold)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 115/208-230 V	Altitude	: 3280 ft
Rated current	: 16.8/9.40-8.40 A	Protection degree	: IP55
L. R. Amperes	: 124/69.6-62.2 A	Cooling method	: IC411 - TEFC
LRC	: 7.4	Mounting	: F-1
No load current	: 4.50/1.94-2.25 A	Rotation ¹	: Both
Rated speed	: 1740 rpm	Noise level ²	: 60.0 dB(A)
Slip	: 3.33 %	Vibration class	: NOT APPLICABLE
Rated torque	: 5.95 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 290 %	Coupling	: Direct
Pull up torque	: 245 %	Approx. weight ³	: 104 lb
Breakdown torque	: 230 %	Painting plan	: 207A
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.15		
Moment of inertia (J)	: 0.2966 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	69.0	76.5	80.0	Load torque	: -
Power Factor	0.96	0.97	0.97	Load inertia (J=GD ² /4)	: -

Bearing type	Drive end	Non drive end	Foundation loads	
	6207-ZZ	6206-ZZ		Max. traction
Lubrication interval	-	-	Max. compression	: -
Lubricant amount	-	-		
Lubricant type	POLYUREA BASED GREASE			

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq			1856015968	
Checked by	AUTOMATICO			Page	Rev.
Date	02/06/2026			1 / 1	0