

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Premium Efficiency (DOE)

Frame	: 56	Locked rotor time	: 40 s (hot) 72 s (cold)
Output	: 0.25 HP (0.18 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 3280 ft
Rated current	: 0.405 A	Protection degree	: IP55
L. R. Amperes	: 1.90 A	Cooling method	: IC411 - TEFC
LRC	: 4.7	Mounting	: F-1/B3R(D)
No load current	: 0.346 A	Rotation <sup>1</sup>	: Both
Rated speed	: 1160 rpm	Noise level <sup>2</sup>	: 50.0 dB(A)
Slip	: 3.33 %	Vibration class	: A
Rated torque	: 1.11 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 190 %	Approx. weight <sup>3</sup>	: 22.5 lb
Pull up torque	: 160 %	Color	: PRIMER ONLY
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0712 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	62.0	68.0	72.0	Load torque	: -
Power Factor	0.42	0.53	0.62	Load inertia (J=GD <sup>2</sup> /4)	: -

Bearing type	Drive end	Non drive end	Foundation loads	Max. traction	: 97 N
	6203-ZZ	6202-ZZ			
Lubrication interval	-	-	Max. compression	: 196 N	
Lubricant amount	-	-			
Lubricant type	MOBIL POLYREX EM				

Notes  
See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
41.2	36.0	38.8	32.7	23.4	21.5	16.5

This revision replaces and cancel the previous one, which must be eliminated.  
 (1) Looking the motor from the shaft end.  
 (2) Measured at 1m and with tolerance of +3dB(A).  
 (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq		1856307316		
Checked by	AUTOMATICO		Page	Rev.	
Date	03/06/2026		1 / 2	0	

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - TEFC - Premium Efficiency (DOE)

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.  
(1) Looking the motor from the shaft end.  
(2) Measured at 1m and with tolerance of +3dB(A).  
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1856307316		
Checked by	AUTOMATICO	Page	Rev.	
Date	03/06/2026	2 / 2	0	