

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W22

Product code : 14089875

Frame	: 182/4T	Locked rotor time	: 9 s (hot) 16 s (cold)
Output	: 3 HP (2.2 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 115/208-230 V	Altitude	: 3280 ft
Rated current	: 24.4/13.5-12.2 A	Protection degree	: IP55
L. R. Amperes	: 188/104-93.9 A	Cooling method	: IC411 - TEFC
LRC	: 7.7	Mounting	: F-1
No load current	: 8.00/3.45-4.00 A	Rotation ¹	: Both
Rated speed	: 3520 rpm	Noise level ²	: 72.0 dB(A)
Slip	: 2.22 %	Vibration class	: NOT APPLICABLE
Rated torque	: 4.41 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 250 %	Coupling	: Direct
Pull up torque	: 210 %	Approx. weight ³	: 94.8 lb
Breakdown torque	: 260 %	Painting plan	: 207A
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.15		
Moment of inertia (J)	: 0.1566 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	80.0	83.0	84.0	Load torque	: -
Power Factor	0.92	0.93	0.93	Load inertia (J=GD ² /4)	: -

Bearing type	Drive end	Non drive end	Foundation loads		
	6207-ZZ	6206-ZZ		Max. traction	: -
	Lubrication interval	-		Max. compression	: -
	Lubricant amount	-			
	Lubricant type	POLYUREA BASED GREASE			

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	farazq	1855266217		
Checked by	AUTOMATICO	Page	Rev.	
Date	01/06/2026	1 / 1	0	