



Velocidad maxima segura:6000 rpm/Max safe speed:6000 rpm					
Apto para trabajar para VFD 1000: 1 CT / Suitable to work for VFD 1000:1 CT					
Placa de identificación adicional para uso del inversor / Nameplate for VFD motor					
Termostato 155°C – Desconexión / Thermal protection to switch off – thermostat 155°C					
Material del eje – SAE/ABNT 1040/45 / Shaft material – SAE/ABNT 1040/45					
Vedación – Anillos V Ring / Sealing – V ring					
Dren automático de goma / Automatic rubber drain plug					
Color Munsell N 1 negro mate / Color Munsell N 1 matte black					
Plan de pintura 207N / Painting plan 207N					
Forma constructiva F-1/B34R(D) / Mounting F-1/B34R(D)					
V.J. PAMENSKY CANADA INC.					

New drawing				OSCARFLORES	MORALESR	RIOMIGUEL	15.01.2025	00
ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER	
EXECUTED	OSCARFLORES	THREE PH. MOTOR ROLLED STEEL PREM. EFF.						
CHECKED	MORALESR	FRAME 56CZ IP55 TENV						
RELEASED	RIOMIGUEL							
REL. DATE	15.01.2025	WEG HUEHUETOCA [Ventas Exportacion]	1634829758		WDD 00		SHEET 1 / 1	

0.75 HP 04 Poles 60 Hz

422517419

A

PRELIMINARY DOCUMENT - Not to be used for installation purposes. Dimensions in inches. XME A3